WORLD INTELLECTUAL PROPERTY ORGANIZATION



(51) Internation: l Patent Classification 6:

> A61F 2444, 2/46, A61B 17/86, 17/16, 17/32, A61L 27/00, B23G 5/00

A1

(11) International Publication Number:

WO 98/55052

(43) International Publication Date:

10 December 1998 (10.12.98)

(21) Inter/national Application Number:

PCT/US98/11159

(22) In'/ernational Filing Date:

3 June 1998 (03.06.98)

(30)/Priority Data:

08/867,963

3 June 1997 (03.06.97)

US

(71) Applicants (for all designated States except US): SDGI HOLDINGS, INC. [US/US]; Suite 508, 300 Delaware Avenue, Wilmington, DE 19801 (US). UNIVERSITY OF FLORIDA TISSUE BANK, INC. [US/US]: 1 Innovation Drive, Alachua, FL 32615 (US).

(72) Inventors; and

(75) Inventors, Applicants (for US only): BIANCHI, John, R. [US/US]; 4621 S.W. 85th Drive, Gainesville, FL 32608 (US). CARTER, Kevin, C. [US/US]; 8502 N.W. 35th Road, Gainesville, FL 32606 (US). ESTES, Bradley, T. [US/US]; 3699 Friar Tuck Road, Memphis, TN 38111 (US). BOYD, Larry [US/US]; 5105 Lynbar Avenue, Memphis, TN 38117 (US). PAFFORD, John, A. [US/US]; 2613 Fox Hill Circle East, Germantown, TN 38139 (US).

(74) Agents: GANDY, Kenneth, A. et al.; Woodard, Emhardt, Naughton, Moriarty & McNett, Bank One Center/Tower, Suite 3700, 111 Monument Circle, Indianapolis, IN 46204 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: OPEN INTERVERTEBRAL SPACER

(57) Abstract

Open chambered spacers, implanting tools and methods are provided. The spacers (500') include a body (505') having a wall (506') which defines a chamber (530') and an opening (531') in communication with the chamber (530'). In one embodiment the wall (506') includes a pair of arms (520'. 521') facing one another and forming a mouth (525') to the chamber (530'). Preferably, one of the arms (520') is truncated relative to the other, forming a channel (526). In one aspect the body (505') is a bone dowel comprising an off-center plug from the diaphysis of a long bone. The tools (800) include spacer engaging means for engaging a spacer and occlusion means for blocking an opening defined in the spacer. In some embodiments, the occlusion means (820) includes a plate (821)extendable from the housing (805). In one specific embodiment the plate (821) defines a groove (822) which is



disposed around a fastener (830) attached to the housing (805) so that the plate (821) is slideable relative to the housing (805).

-39-

What is claimed is:

5

- 1. A hollow intervertebral spacer, comprising: an elongated body having an outer surface and a longitudinal axis along a length of said body and defining a chamber therethrough along a second axis substantially perpendicular to said longitudinal axis;
 - a first arm connected to said body;
 - an opposite second arm connected to said body and facing said first arm; and
- said first arm and said second arm forming a mouth to said chamber.
 - 2. The spacer of claim 1 wherein said body further comprises:
- a tool engaging end defining a tool engaging hole for receiving a driving tool for implanting the spacer.
 - 3. The spacer of claim 2 wherein said anterior surface further defines a slot surrounding said tool engaging hole.
 - 4. The spacer of claim 1 wherein said outer surface defines threaded bone engaging portions.
- 5. The spacer of claim 1 wherein said wall is curved and said chamber is substantially C-shaped.
 - 6. The spacer of claim 1 wherein said body is composed of a porous material.
- 7. The spacer of claim 1 wherein said body is composed substantially of cortical bone.
 - 8. The spacer of claim 1 wherein said first arm is truncated relative to said second arm.

-40-

- 9. The spacer of claim 3 wherein said outer surface defines threaded bone engaging portions and said body is composed of cortical bone.
- 10. The spacer of claim 4 wherein said spacer is a bone dowel obtained from the diaphysis of a long bone having a medullary canal, said chamber including a portion of the canal.
 - 11. The spacer of claim 1, further comprising an osteogenic material packed within said chamber.
- 12. The spacer of claim 11 wherein said osteogenic material comprises autograft, allograft, xenograft, demineralized bone, a calcium phosphate material, a bioceramic, bioglass, an osteoinductive factor or mixtures of thereof.
- 13. An interbody fusion spacer, comprising:
 a body having a wall defining a chamber, the body
 defining an opening in communication with said chamber, said
 wall having a first arm and an opposite second arm facing
 said first arm, said first arm and said second arm forming a
 mouth to said chamber, wherein said first arm is truncated
 relative to said second arm.
 - 14. The spacer of claim 13 wherein said body further comprises:
- a tool engaging end defining a tool engaging hole for receiving a driving tool for implanting the spacer.
 - 15. The spacer of claim 14 wherein said anterior surface further defines a slot surrounding said tool engaging hole.

-41-

16. The spacer of claim 13 wherein said body further comprises:

an outer surface defining threaded bone engaging surfaces.

- 5 17. The spacer of claim 13 wherein said wall is curved and said chamber is C-shaped.
 - 18. The spacer of claim 13 wherein said spacer comprises cortical bone.
- 19. The spacer of claim 13 further comprising an osteogenic material packed within said chamber.

15

- 20. A graft comprising an elongated body consisting essentially of cortical bone, said body having an outer surface and a longitudinal axis along a length of said body and defining a chamber therethrough along a second axis substantially perpendicular to said longitudinal axis, said body further defining a channel defined along said longitudinal axis and in communication with said chamber and said outer surface.
- 21. The graft of claim 20 wherein said outer surface 20 defines threaded bone engaging surfaces.
 - 22. The graft of claim 20 further comprising an osteogenic material packed within said chamber.
- 23. A hollow intervertebral spacer, comprising:
 a cylindrical body having a wall, said wall having an

 outer surface and defining a chamber and an opening in
 communication with said chamber; and a channel defined in
 said wall in communication with said chamber and said outer
 surface.

-42-

- 24. The spacer of claim 23 wherein said outer surface defines threaded bone engaging portions.
- 25. A bone graft having a C-shaped wall defining a chamber.
- ⁵ 26. The spacer of claim 25 wherein said graft is a bone dowel obtained from the diaphysis of a long bone having a medullary canal, said chamber including a portion of the canal.
- 27. A "C"-shaped dowel substantially composed of cortical bone.
 - 28. The "C"-shaped dowel of claim 27 comprising a bone plug obtained from the diaphysis of a long bone, said dowel having a substantially "C"-shaped chamber.
- 29. The "C"-shaped dowel of claim 28 having a chamfered insertion end.
 - 30. The "C"-shaped dowel of claim 28 further comprising a tool engaging end defining an instrument attachment hole.
- 31. The "C"-shaped dowel of claim 30 wherein the tool engaging end also defines a driver slot surrounding said hole.
 - 32. The "C"-shaped dowel of claim 28 further comprising am external feature machined into an outer surface of the dowel.
- 33. The "C"-shaped dowel of claim 32 wherein said feature includes a groove.

-43-

- 34. The "C"-shaped dowel of claim 32 wherein said feature includes threads formed along a portion of the length of the dowel.
- 35. The "C"-shaped dowel of claim 27 having a length of between about 8mm to about 36mm.
 - 36. The "C"-shaped dowel of claim 35 having a diameter of between about 10mm and about 24mm.
 - 37. The "C"-shaped dowel of claim 28 further comprising an osteogenic composition packed within said chamber.
- 38. The "C"-shaped dowel of claim 37 wherein said osteogenic composition comprises autogenous bone, bone morphogenetic protein, a calcium phosphate composition or a mixture of these.
- 39. The "C"-shaped dowel of claim 27 obtained as an off-center transverse plug from the shaft of a donor's fibula, radius, ulna, humerus, femur or tibia.

20

- 40. A method of making a dowel which comprises machining an off-center transverse plug from the diaphysis of a donor's fibula, radius, ulna, humerus, femur or tibia, said plug having a diameter of between about 10mm and about 24mm and a depth (length) of between about 8mm and about 30mm such that the resulting dowel has, running through it, perpendicular to the long axis of the dowel, a substantially "C"-shaped chamber.
- 25 41. The method of claim 40 further comprising chamfering one end of said plug to form a generally curved surface for ease of insertion of the dowel into an intervertebral cavity.

WO 98/55052

10

25

-44-

PCT/US98/11159

- 42. The method of claim 40 further comprising machining an instrument attachment hole into one end of the dowel.
- 43. The "C"-shaped dowel of claim 27 prepared by a process comprising machining an off-center transverse plug from the diaphysis of a donor's fibula, radius, ulna, humerus, femur or tibia, said plug having a diameter of between about 10mm and about 24mm and a length of between 8mm and about 36mm such that the resulting dowel has, running through it, perpendicular to the long axis of the dowel, a substantially "C"-shaped chamber.
 - 44. The "C"-shaped dowel of claim 27 having an outer surface defining a surface feature .
 - 45. The "C"-shaped dowel of claim 44 wherein said feature includes a groove.
- 15 46. The "C"-shaped dowel of claim 44 wherein said feature includes threads formed along a portion of the length of the dowel.
 - 47. The "C"-shaped dowel of claim 46 wherein said thread has a pitch of about 0.1".
- 20 48. A spacer insertion tool, comprising:
 - a housing having a proximal end and an opposite distal end and defining a passageway between said proximal end and said distal end;
 - a shaft having a first end and an opposite second end, said shaft disposed within said passageway with said first end adjacent said distal end, said first end defining a spacer engager; and

an occlusion member extendable from said distal end of

-45-

said housing for blocking an opening defined in the spacer when said spacer engager is engaged to the spacer.

49. The tool of claim 48, further comprising a fastener attached to said shaft and wherein said occlusion member includes a plate defining a groove, said groove disposed around said fastener so that said plate is slidable relative to said housing.

5

- 50. The tool of claim 49 wherein said plate has a curved superior surface which approximates the outer surface of the spacer when said spacer engaging means is engaged to the spacer and said occlusion means is blocking the opening of the spacer.
 - 51. The tool of claim 48 wherein said shaft is slidingly disposed within said passageway.
- 15 52. The tool of claim 48 wherein said spacer engager is threaded for mating engagement with a threaded hole in a spacer.
 - 53. The tool of claim 48 wherein said spacer engager is a hex for mating engagement with an internal hex in a spacer.
- 54. An insertion tool for inserting a spacer into an intervertebral space, comprising:

spacer engaging means for engaging the spacer; and occlusion means separate from said spacer engaging means for blocking an opening defined in the spacer.

55. The tool of claim 54 wherein said occlusion means includes a plate, said plate having a curved superior surface which approximates the outer surface of the spacer when said spacer engaging means is engaged to the spacer and said occlusion means is blocking the opening of the spacer.

WO 98/55052

-46-

PCT/US98/11159

- 56. The tool of claim 54 wherein said spacer engaging means includes a post for engaging a hole in the spacer.
- 57. The tool of claim 56 wherein said post is threaded for mating engagement with a threaded hole in a spacer.
- 5 58. The tool of claim 56 wherein said post is a hex for mating engagement with an internal hex in a spacer.
 - 59. The tool of claim 74 wherein said spacer engaging means is a pair of prongs having opposite, facing spacer engaging members for grasping an outer surface of the spacer.
- 10 60. A driving tool for implanting an interbody spacer in a space between adjacent vertebrae, the spacer including a body defining a chamber and an opening in communication with the chamber, the body having a pair of arms facing one another and forming a mouth to the chamber, and an anterior surface defining a tool engaging hole, the tool comprising:

spacer engaging means for engaging the tool engaging hole; and

occlusion means for blocking said mouth.

- 61. The tool of claim 60 further comprising a housing 20 and wherein said occlusion means is extendable from said housing.
 - 62. The tool of claim 60 wherein said spacer engaging means is a threaded post for threading engagement with the tool engaging hole.
- 25 63. A method for fusing two adjacent vertebrae, comprising the steps of:

providing a spacer, the spacer including a body having a

-47-

wall, said wall having an outer surface and defining a chamber and an opening in communication with said chamber, and a channel defined in said wall in communication with said chamber and said outer surface;

preparing the vertebrae and the intervertebral space between the vertebrae to receive the spacer;

5

10

15

20

25

30

placing the spacer into the intervertebral space after the preparing step so that the opening is in communication with at least one of the vertebrae; and

packing osteogenic material into the channel after the placing step.

64. A method for fusing two adjacent vertebrae, comprising the steps of:

providing a spacer, the spacer including a body having a wall, said wall having an outer surface and defining a chamber and an opening in communication with said chamber, and a channel defined in said wall in communication with said chamber and said outer surface;

preparing the vertebrae and the intervertebral space between the vertebrae to receive the spacer;

packing osteogenic material into the chamber; blocking the channel; and

placing the spacer into the intervertebral space after the blocking step so that the opening is in communication with at least one of the vertebrae.

65. The method of claim 64 further comprising:

implanting a second spacer into the intervertebral space after the placing step, the second spacer having a body having a wall, said wall having an outer surface and defining a chamber and an opening in communication with said chamber, and a channel defined in said wall in communication with said chamber and said outer surface; and

orienting the first spacer and the second spacer so that

-48-

the channels of the first and second spacers face one another.

- 66. The method of claim 65 further comprising packing an osteogenic material into the channels of the first and second spacers.
 - 67. The method of claim 64,

10

further comprising providing a tool of claim 27; engaging the spacer engager of the tool to the spacer; and wherein the blocking step includes extending the occlusion member to block the channel.

- 68. The spacer of claim 1 wherein said body is composed of a metal, a ceramic, a polymer or a composite or alloy thereof.
- 69. The spacer of claim 13 wherein said body is composed of a metal, a ceramic, a polymer or a composite or alloy thereof.
 - 70. The spacer of claim 1 wherein said outer surface includes a curved portion and a flattened portion.
- 71. The spacer of claim 13 wherein said body further
 20 comprises an outer surface that defines a curved portion and
 a flattened portion.

rnational Application No PCT/US 98/11159

	<u> </u>	FC1/U3 9	6/11159
A. CLASSI IPC 6	IFICATION OF SUBJECT MATTER	'86 A61B17/16 A61	B17/32
According to	to International Patent Classification (IPC) or to both national classifi	cation and IPC	
	SEARCHED		
Minimum do IPC 6	ocumentation searched (classification system followed by classifical $A61F$	tion symbols)	
Oocumenta	ation searched other than minimum documentation to the extent that	such documents are included in the fields s	earched
Electronic d	data base consulted during the international search (name of data b	ase and, where practical, search terms use	d)
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the re	elevant passages	Relevant to claim No.
Y	US 4 950 296 A (MCINTYRE) 21 Aug	just 1990	1,5-7, 11,12, 23,25,
A .	see column 2, line 22 - column 3	27,68,70 10,13, 18-20, 22,26, 28,37-40	
Υ Α	WO 96 28118 A (KUSLICH) 19 Septe	1,5-7, 11,12, 23,25, 27,68,70	
••••••••••••••••••••••••••••••••••••••	see page 8, line 30 - page 9, li figures 10-13 	-/	13,17,20
X Furt	ther documents are listed in the continuation of box C.	X Patent family members are lister	l in annex.
"A" docume consic filing c filing c "L" docume which citation "O" docume other i "P" docume later th	ent which may throw doubts on priority claim(s) or is cited to establish the publication date of another in or other special reason (as specified) lent referring to an oral disclosure, use, exhibition or means ent published prior to the international filing date but han the priority date claimed	"T" later document published after the im or priority date and not in conflict with cited to understand the principle or invention "X" document of particular relevance; the cannot be considered novel or canninvolve an inventive step when the cannot be considered to involve an document is combined with one or ments, such combination being obvin the art. "&" document member of the same pater	th the application but theory underlying the claimed invention of the considered to document is taken alone claimed invention inventive step when the nore other such docuous to a person skilled
	actual completion of theimernational search 5 September 1998	Date of mailing of the international set	earch report
Name and r	mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Klein, C	

PCT/US 98/11159

		PCT/US 98/11159		
C.(Continu	ation) DOCUMENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
A	US 4 877 020 A (VICH) 31 October 1989 see the whole document	2,4,14, 16,21, 24,30, 32,34, 42,46, 48,54,60		
A	EP 0 307 241 A (BRANTIGAN) 15 March 1989	2-4,6,9, 11,12, 14-16, 19,21, 22,24, 30-34, 37,38, 48,54, 60,68,69		
	see the whole document	33,03,03		
Α	GB 2 207 607 A (A W SHOWELL (SURGICRAFT)) 8 February 1989 see the whole document	5,17,25, 27		
Α	DE 37 41 493 A (MAN ROLAND DRUCKMASCHINEN) 22 June 1989 see the whole document	5,17,25, 27		
A	US 5 329 846 A (BONUTTI) 19 July 1994 see the whole document	40		
A	US 3 848 601 A (MA) 19 November 1974 see the whole document	40,48, 54,60		
Α	US 5 062 845 A (KUSLICH) 5 November 1991 see the whole document	40		
P,A	WO 97 25945 A (UNIVERSITY OF FLORIDA, TISSUE BANK) 24 July 1997 see the whole document	1,13,20, 23,40		
A	EP 0 734 703 A (DANEK MEDICAL) 2 October 1996 cited in the application	•		
Α	US 5 015 247 A (MICHELSON) 14 May 1991 cited in the application			
Α	EP 0 077 159 A (ATKINS) 20 April 1983			

rternational application No. PCT/US 98/11159

INTERNATIONAL SEARCH REPORT

Box I	Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)
This Inte	rnational Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:
1. X	Claims Nos.: 63-67 because they relate to subject matter not required to be searched by this Authority, namely: Rule 39.1(iv) PCT - Method for treatment of the human or animal body by
2.	Claims Nos.: because they relate to parts of the International Application that do not comply with the prescribed requirements to such
	an extent that no meaningful International Search can be carried out, specifically:
3.	Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).
Box II	Observations where unity of invention is lacking (Continuation of item 2 of first sheet)
This Inte	mational Searching Authority found multiple inventions in this international application, as follows:
1.	As all required additional search fees were timely paid by the applicant, this International Search Report covers all
2.	As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment
	of any additional fee.
3.	As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
. * <i>2</i> 	
4. [No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
Remark	on Protest The additional search fees were accompanied by the applicant's protest. No protest accompanied the payment of additional search fees.

Information on patent family members

PCT/US 98/11159

	atent document d in search report	t	Publication date		tent family ember(s)		Publication date
US	4950296	A	21-08-1990	NONE			
WO	9628118	A	19-09-1996	US AU AU CA EP	5591235 689713 4997296 2214509 0814732	B A A	07-01-1997 02-04-1998 02-10-1996 19-09-1996 07-01-1998
US	4877020	Α	31-10-1989	DE JP	3505567 61135652		05-06-1986 23-06-1986
EP	307241	A	15-03-1989	US CA DE US AU AU JP WO	4834757 1292596 3876909 4878915 614609 3436389 3503133 8909035	A A B A T	30-05-1989 03-12-1991 04-02-1993 07-11-1989 05-09-1991 16-10-1989 18-07-1991 05-10-1989
GB	2207607	Α	08-02-1989	DE EP JP JP JP US	3864946 0302719 1303148 2114682 8022294 4904261	A A C B	24-10-1991 08-02-1989 07-12-1989 06-12-1996 06-03-1996 27-02-1990
DE	3741493	Α	22-06-1989	NONE			
US	5329846	Α	19-07-1994	US US	5545222 5662710		13-08-1996 02-09-1997
US	3848601	Α	19-11-1974	NONE			
US	5062845	Α	05-11-1991	US CA US CA	5015255 2007210 5445639 2007209	A,C A	14-05-1991 10-11-1990 29-08-1995 10-11-1990
WO	9725945	A	24-07-1997	AU	1700597	Α	11-08-1997

Information on patent family members

. /national Application No PCT/US 98/11159

_						- 0, 11101
	atent document d in search report		Publication date		Patent family . member(s)	Publication date
EP	734703	Α	02-10-1996	US	5669909 A	23-09-1997
				ÜS	5782919 A	21-07-1998
				AU	2132897 A	10-09-1997
				AU	4829296 A	10-10-1996
				AU	4829496 A	10-10-1996
				CA	2171907 A	28-09-1996
				CA	2171921 A	28-09-1996
				CN	1143488 A	26-02-1997
				CN	1143489 A	26-02-1997
				JP	8266565 A	15-10-1996
				JP	8294495 A	12-11-1996
				NO	961213 A	30-09-1996
				NO	961214 A	30-09-1996
				WO	9731517 A	28-08-1997
US	5015247	Α	14-05-1991	AU	3838789 A	12-01-1990
				CA	1332999 A	15-11-1994
				EP	0419564 A	03-04-1991
				EP	0712607 A	22-05-1996
				US	5484437 A	16-01-1996
				WO	8912431 A	28-12-1989
				US	5593409 A	14-01-1997
				US	5772661 A	30-06-1998
				US	5785710 A	28-07-1998
				US	5505732 A	09-04-1996
				US	5797909 A	25-08-1998
				US 	5741253 A	21-04-1998
ΕP	77159	Α	20-04-1983	JP	58078653 A	12-05-1983